

DECLARATION OF PERFORMANCE

DoP No. 0679-CPR-0911 - GB

(Version 1)

- 1. Unique identification code of the product-type: ELEMATIC PRIME BLOK
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-13/0739 (31/05/2013), Annex 1 -Batch number: see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Bonded anchor for use in conjuction with Post installed rebar connections
For use in	Non cracked concrete : Ø8,Ø10,Ø12,Ø14,Ø16,Ø20 Concrete C12/15 to C50/60
Option / Category	/ 2
Loading	Static and quasi static
Material	Rebar class B & C according to EN 1992-1-1
Temperature range if applicable	-40° + 40°C

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ITW CONSTRUCTION PRODUCTS ITALY SRL Viale Regione Veneto, 5 -35127 Padova - Italia

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 1
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

CSTB - Centre Scientifique et Technique du Bâtiment (France)

issued ETA-13/0739 (31/05/2013)

on the basis of TR023,

The notified body 0679-CPR performed under System 1

- i. Determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- ii. Initial inspection of the manufacturing plant and of factory production control;
- iii. Continuous surveillance, assessment and evaluation of factory production control under system1

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
characteristic resistance for tension	EN 1992-1-1	ETA-13/0739 Annex 10	
characteristic resistance for shear	EN 1992-1-1	NPD	
minimum spacing and minimum edge distance	EN 1992-1-1	ETA-13/0739 Annex 6	TR 023
displacement for serviceability limit state	EN 1992-1-1	ETA-13/0739 Annex 10 &PD	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Padova, 01/07/2013

ANDREA SANTINI General Manager





DECLARATION OF PERFORMANCE

DoP No. 0679-CPR-0907 - GB

(Version 1)

- 1. Unique identification code of the product-type: ELEMATIC PRIME BLOK
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-13/0737 (31/05/2013), Annex 1 -Batch number: see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Bonded anchor with threaded rods and rebars
For use in	Non cracked concrete : M8,M10,M12,M16,M20,M24 Concrete C20/25 to C50/60
Option / Category	7/ 1
Loading	Static and quasi static
Material	Zinc plated steel for dry internal conditions only <u>Stainless steel (A4)</u> for internal and external use without particular aggressive conditions <u>Highly corrosion resistant steel</u> for internal and external use with aggressive conditions
Temperature range if applicable	-40° + 40°C

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ITW CONSTRUCTION PRODUCTS ITALY SRL Viale Regione Veneto, 5 -35127 Padova - Italia

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 1
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

CSTB - Centre Scientifique et Technique du Bâtiment (France)

issued ETA-13/0737 (31/05/2013)

on the basis of ETAG-001-5,

The notified body 0679-CPR performed under System 1

- i. Determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- ii. Initial inspection of the manufacturing plant and of factory production control;
- iii. Continuous surveillance, assessment and evaluation of factory production control under system1

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
characteristic resistance for tension	TR 029 (for studs)	ETA-13/0737 Annex 7	
characteristic resistance for shear	TR 029 (for studs)	ETA-13/0737 Annex 8	
minimum spacing and minimum edge distance	TR 029 (for studs)	ETA-13/0737 Annex 6	ETAG 001-1,5
displacement for serviceability limit state	TR 029 (for studs)	ETA-13/0737 Annex 7 & 8	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Padova, 01/07/2013

ANDREA SANTINI General Manager





DECLARATION OF PERFORMANCE

DoP No. 0679-CPR-0908 - GB

(Version 1)

- 1. Unique identification code of the product-type: ELEMATIC PRIME BLOK
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-13/0741 (31/05/2013), Annex 1 -Batch number: see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Bonded anchor
For use in	Masonry : M8,M10,M12 Calcium silicate masonry, perforated clay bricks, aggregates concrete hollow masonry
Option / Category	B,C
Loading	Static and quasi static
Material	<u>Zinc plated steel</u> for dry internal conditions only <u>Stainless steel (A4)</u> for internal and external use without particular aggressive conditions <u>Highly corrosion resistant steel</u> for internal and external use with aggressive conditions
Temperature range <i>if applicable</i>	-40° + 40°C

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ITW CONSTRUCTION PRODUCTS ITALY SRL Viale Regione Veneto, 5 -35127 Padova - Italia

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 1
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

CSTB - Centre Scientifique et Technique du Bâtiment (France)

issued ETA-13/0741 (31/05/2013)

on the basis of ETAG-029,

The notified body 0679-CPR performed under System 1

- i. Determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- ii. Initial inspection of the manufacturing plant and of factory production control;
- iii. Continuous surveillance, assessment and evaluation of factory production control under system1

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
characteristic resistance for tension	ETAG 029 - Annex C	ETA-13/0741 Annex 9	
characteristic resistance for shear	ETAG 029 - Annex C	ETA-13/0741 Annex 9	
minimum spacing and minimum edge distance	ETAG 029 - Annex C	ETA-13/0741 Annex 11	ETAG 001-1,5
displacement for serviceability limit state	ETAG 029 - Annex C	ETA-13/0741 Annex 9 & 9	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Padova, 01/07/2013

ANDREA SANTINI General Manager

