



DECLARATION OF PERFORMANCE

DoP No. 0679-CPD-0221 - GB
(Version 1)

1. Unique identification code of the product-type: **ELEMATIC TC LP Ev 410**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
ETA-05/0276 (05/06/2012), Annex 2 - Annex 3
Batch number: see packaging of the product.
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

| | |
|--|---|
| Generic type | Bonded anchor with threaded rods or internal sleeve |
| For use in | Non cracked concrete : M8,M10,M12,M16,M20,M24,M30 (studs) and M8,M10,M12,M16,M20 (ATP) Concrete C20/25 to C50/60 |
| Option / Category | 7/ 2 |
| Loading | Static and quasi static |
| Material | <u>Zinc plated steel</u> for dry internal conditions only <u>Stainless steel (A4)</u> for internal and external use without particular aggressive conditions <u>Highly corrosion resistant steel</u> for internal and external use with aggressive conditions |
| Temperature range if applicable | -40 +120°C |

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
ITW CONSTRUCTION PRODUCTS ITALY SRL Viale Regione Veneto, 5 -35127 Padova - Italia
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 1**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

CSTB - Centre Scientifique et Technique du Bâtiment (France)

issued **ETA-05/0276 (05/06/2012)**

on the basis of **ETAG-001-5,**

The notified body **0679-CPR** performed under **System 1**

- i. Determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- ii. Initial inspection of the manufacturing plant and of factory production control;
- iii. Continuous surveillance, assessment and evaluation of factory production control under system1

9. Declared performance:

| Essential Characteristics | Design Method | Performance | Harmonized Technical Specification |
|---|---|---|------------------------------------|
| characteristic resistance for tension | TR 029 (for studs) Annex C (for ATP) | ETA-05/0276 Annex 9 ETA-05/0276 Annex 11 | ETAG 001-1,5 |
| characteristic resistance for shear | TR 029 (for studs) Annex C (for ATP) | ETA-05/0276 Annex 10 ETA-05/0276 Annex 12 | |
| minimum spacing and minimum edge distance | TR 029 (for studs) Annex C (for ATP) | ETA-05/0276 Annex 8 ETA-05/0276 Annex 8 | |
| displacement for serviceability limit state | TR 029 (for studs) Annex C (for ATP) | ETA-05/0276 Annex 9 &10 ETA-05/0276 Annex 11 &12 | |

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Padova, 01/07/2013

ANDREA SANTINI
General Manager

